

BATTERIES

- Mercury free
- Extended operation life
- Suitable for use in digital metres, calculators, torches and security equipment
- Higher capacity than zinc chloride batteries
- Suitable for applications where high intermittent currents are required.

ALKALINE



SECTION 7

ORDERING INFORMATION

Ordering Code	Voltage (V)	Can Size	Dimensions (mm)
LR20X	1.5	D	ø34.2 x H61.5
LR14X	1.5	C	ø26.2 x H50
LR6X	1.5	AA	ø14.5 x H50.5
LR03XX	1.5	AAA	ø10.5 x H44.5
6LR61X	9	PP3	L26.5 x W17.5 x H48.5

BATTERIES



- Rechargeable
- Custom battery packs available
- 5 can sizes
- Suitable for use in camera, instruments or memory backup
- Ideal for security applications

NICKEL METAL HYDRIDE NiMH



ORDERING INFORMATION

Ordering Code	Size	Nominal Voltage (V)	Capacity	Dimensions		Standard Charge		Weight (g)
			0.2C disc (mAh)	Dia (mm)	Height (mm)	Current (mA)	Time (hour)	
AAA600	AAA	1.2	600	10.1 +/- 0.1	44.2 +/- 0.3	60	15	13
AAA650	AAA	1.2	650	10.1 +/- 0.1	44.2 +/- 0.3	65	15	13.5
AAA700	AAA	1.2	700	10.1 +/- 0.1	44.2 +/- 0.3	70	15	14
AAA800	AAA	1.2	800	10.1 +/- 0.1	44.2 +/- 0.3	80	15	14.5
AAA900	AAA	1.2	900	10.1 +/- 0.1	44.2 +/- 0.3	90	15	15
AA600	AA	1.2	600	14.1 +/- 0.1	49.7 +/- 0.3	60	15	15
AA800	AA	1.2	800	14.1 +/- 0.1	49.7 +/- 0.3	80	15	21
AA1000	AA	1.2	1000	14.1 +/- 0.1	49.7 +/- 0.3	100	15	24
AA1200	AA	1.2	1200	14.1 +/- 0.1	49.7 +/- 0.3	120	15	25
AA1300	AA	1.2	1300	14.1 +/- 0.1	49.7 +/- 0.3	130	15	25.5
AA1500	AA	1.2	1500	14.1 +/- 0.1	49.7 +/- 0.3	150	15	26.5
AA1600	AA	1.2	1600	14.1 +/- 0.1	49.7 +/- 0.3	160	15	27
AA1800	AA	1.2	1800	14.1 +/- 0.1	50.2 +/- 0.3	180	15	28
AA2000	AA	1.2	2000	14.1 +/- 0.1	50.2 +/- 0.3	200	15	28.5
AA2200	AA	1.2	2200	14.1 +/- 0.1	50.2 +/- 0.3	220	15	28.5
AA2300	AA	1.2	2300	14.1 +/- 0.1	50.2 +/- 0.3	230	15	29
AA2500	AA	1.2	2400	14.1 +/- 0.1	50.2 +/- 0.3	240	15	29
C2400	C	1.2	2400	24.9 +/- 0.1	49.7 +/- 0.3	240	15	70
C3300	C	1.2	3300	24.9 +/- 0.1	49.7 +/- 0.3	330	15	78
C3700	C	1.2	3700	24.9 +/- 0.1	49.7 +/- 0.3	370	15	83
C4000	C	1.2	4000	24.9 +/- 0.1	49.7 +/- 0.3	400	15	85
C4500	C	1.2	4500	24.9 +/- 0.1	49.7 +/- 0.3	450	15	88.5
D2400	D	1.2	2400	32.2 +/- 0.1	60.5 +/- 0.5	240	15	98
D2800	D	1.2	2800	32.2 +/- 0.1	60.5 +/- 0.5	280	15	98
D5000	D	1.2	5000	32.2 +/- 0.1	60.5 +/- 0.5	500	15	120
D8000	D	1.2	8000	32.2 +/- 0.1	60.5 +/- 0.5	800	15	156
D9000	D	1.2	9000	32.2 +/- 0.1	60.5 +/- 0.5	900	15	161
9V160	9V	8.4	160	25.6 x 16.5 x 48		16	15	45
9V200	9V	8.4	200	25.6 x 16.5 x 48		20	15	54

AA, AAA and PP3 Battery Chargers available for NiMH batteries available on request

Custom made battery packs available on request.